Excel 24 Way Vertical PDU 20x C13 4x C19 Socket Passive 32A IEC 60309 Plug

Part Code: 555-232

sales@excel-networking.com
excel-networking.com

CIBSE TM65 Embodied Carbon: 37.382 kg CO2e



Main Features

/ Choice of C13 and C19 sockets

/ CE compliant, RoHS complaint

/ External earth facility

/ 3 metre PVC input lead is terminated with a 32 Amp rated IEC 60309 2P+E plug

/ 32A Master air circuit breaker

/ CIBSE TM65 Embodied Carbon: 37.382 kg CO2e

Product Overview

Excel range of power distribution units are designed for installation and use within 19" networking cabinets and enclosures. Each unit comprises a high quality aluminium extruded housing into which are loaded up to 24 sockets.

The range of units are higher density vertical mounted with each unit fitted with a 32A master air circuit breaker and LED indicator to confirm power to the unit.

Product Specifications

This data sheet was generated at 10:42am 10th November 2026 and is subject to change at any time.

Excel 24 Way Vertical PDU 20x C13 4x C19 Socket Passive 32A IEC 60309 Plug

Part Code: 555-232

sales@excel-networking.com
excel-networking.com

Feature	Values
Mounting direction	**Vertical**
Electrical connection	**Connecting cord with plug**
Type of electric plug connection	**32 Amp - EN6039 Style (BS4343)**
Cable length	**3 m**
Number of C13 socket outlets	**20**
Number of C19 socket outlets	**4**
Length	**1375 mm**
Width	**44.4 mm**
Height	**62 mm**
Supply voltage	**230 V**
Surge Protected	**yes**
With LED indication	**yes**
With mounting bracket	**yes**

Standards

Applicable standard	Detail
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
BS 1363-2:2023	13 A plugs, socket outlets, adaptors and connection units. Part 2: 13 A switched and unswitched socket-outlets - Specification
IEC 60884-1:2002 + AMD1:2006 + AMD2:2013 CSV	Plugs and socket-outlets for household and similar purposes - Part1: General requirements

This data sheet was generated at 10:42am 10th November 2026 and is subject to change at any time.

Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
555-230	**Excel 16 Way Vertical PDU 12x C13 4x C19 Socket Passive 32A IEC 60309 Plug**
555-231	**Excel 20 Way Vertical PDU 16x C13 4x C19 Socket Passive 32A IEC 60309 Plug**
555-232	**Excel 24 Way Vertical PDU 20x C13 4x C19 Socket Passive 32A IEC 60309 Plug**

This data sheet was generated at 10:42am 10th November 2026 and is subject to change at any time.