ZEISOPM

Small but complete

OPMVFLLEDCable Test





MORE COMFORTABLE

WE CONSIDER EVERY DETAIL FOR A COMFORTABLE USE FINALLY ACHIEVE A TOUGH AND BUTTERY SOFT USER TOUCH



Type-C interface

Charge everywhere



Lithium battery

Stable power management, safer charging and safer use

- 3h quick charge
- 4h battery OPM
- 12 extra long 2μm/5μm full power shutdown state)



High-precisionOPM

850/1300/1310/1490/1550/1625nm

2.5mm universal connector for FC, SC, ST adapters



Stable and strong light source

Easily penetrate long-distance optical fibers

Use together to improve work efficiency



SHORT PRESS TO SWITCH VFL OUTPUT MODE.
OUTPUT MODE: ON/ALERT/OFF

CABLE TEST MODULE

SHORT PRESS TO TEST CONTINUITY AND TRACE THE CABLE FAULT POINT, CUT THE FIBER TO THE FAULT POINT AND CONNECT AGAIN. THEY TAKE A PATTERN, WHICH CAN TAL WITHOUT A GOOD FAMILY

Hide without revealing

Built-in remote cable module, integrated with the host.



Good helper at night

Equipped with a high-brightness flashlight, convenient for use in dark environment.

SHORT PRESS TO TURN ON/OFF LED LIGHT.



Store and View at any time

500 loop coverage

Press the up and down keys to scroll through the records

Wavelength memory function

Last wavelength memory, when turn on the machine

No fear of dim surroundings

Click ON/OFF button, start backlight function.

User self-calibra -tion function

DIY self adjustment More flexible measurement

When the device is off, long press and key to enter the offset setting.

Thereafter, short press the up and down buttons to adjust the offset value (-5.1dB, 0.1dB per step), short press confirm to confirm the setting.

Energy saving function

Automatic shutdown: to turn on the device automatically shutdown, automatic shutdown after 10 minutes of inactivity. If no need, long press, turn off the device by operating when turn on.

Wavelength switching

short press to switch unit

or check reference(dBT) value

Mini, portable and light

front

back

size:100x59x28mm

side

Product parameters

Model	ZS-20C-V20
PD Type	InGaAs
OPM Connector	2.5mmUniversal connector
Calibrated Wavelengths	850/1300/1310/1490/1550/1625nm
Display Range	-50~+10dBm
Resolution	0.01dB
Accuracy*	±0.2dB
Modulation Test	270/330Hz/2kHz
VFL Connector	2.5mmUniversal connector
VFL Power	20mW
LEDS	Yes
Ex-45 Cable Test	Yes
Interface	Type-C
Battery	Lithium battery
Storage Temper ature	-20~60℃, < 90%RH
Operating Temp erature	10~50℃, < 90%RH
Weight	95g
Size	100mmx59mmx28mm

* at 20±3℃, CW, with FC connector, -10dBm

Packing List

Box×1 OPM×1 Manual×1 Type-C×1 Lanyard×1